

Idle Roller Oil

Protection oil for rollers running idle

KEY CHARACTERISTICS

- Flashpoint: 120 °C
- Specific density: 0,833 g/ml
- Liquid
- Suited for NBR rubber
- For sheetfed, heatset and coldset application
- Can be used at high speed

PACKAGING

12 x 1L plastic bottle
4 x 5L jerrycan
25L jerrycan

INSTRUCTIONS FOR USE

Apply the roller oil undiluted on the ink roller. Repeat during longer press runs.

TRANSPORT & STORAGE

Protect against extreme weather conditions.

Do not store at temperature above 35 °C or below -10 °C.

Take all necessary precautions to avoid environmental pollution due to accidental leakage.

FEATURES AND BENEFITS

Prevents friction of rollers running idle

- No heat build up
- No wear of the roller surface

Free of chlorinated and aromatic hydrocarbons

- Safer and lower environmental impact

Version 1.0, state 19/09/2011 - All data contained in this technical information sheet is based upon lab tests and practical experience. The user is aware that user specific circumstances may influence the results. This technical information sheet is made for information purposes only and it does not constitute a warranty or guarantee in relation to the correctness or completeness of the data. Errors, omissions and literal mistakes excepted, subject to modifications at any time. The user acknowledges that the data contained herein is only effective as long as no updated technical information sheet is issued which replaces and supersedes any former version of this technical information sheet.