

# Antistat Spray

**Antistatic liquid for machine parts**

## KEY CHARACTERISTICS

- For sheetfed, heatset and coldset application
- Anti static effect

## PACKAGING

12 x 1L plastic bottle

## INSTRUCTIONS FOR USE

Spray onto machine components or materials.

## TRANSPORT & STORAGE

Protect against extreme weather conditions.

Do not store at temperature above 35 °C or below -10 °C.

Take all necessary precautions to avoid environmental pollution due to accidental leakage.

## FEATURES AND BENEFITS

### Fast evaporation

- Does not leave residues
- Leaves a dry surface

### Neutralises static electricity

- Safe post press

Version 1.0, state 7/04/2011 - All data contained in this technical information sheet is based upon lab tests and practical experience. The user is aware that user specific circumstances may influence the results. This technical information sheet is made for information purposes only and it does not constitute a warranty or guarantee in relation to the correctness or completeness of the data. Errors, omissions and literal mistakes excepted, subject to modifications at any time. The user acknowledges that the data contained herein is only effective as long as no updated technical information sheet is issued which replaces and supersedes any former version of this technical information sheet.

FUJIFILM Europe NV  
Europark-Noord 21-22  
9100 Sint-Niklaas  
Belgium

T +32 3 760 02 00  
F +32 3 776 91 22  
marketing\_feb@fujifilm.eu  
www.fujifilm.eu/feb

**FUJIFILM**