

# GUMMIN

**Natural based gum for manual and mechanical application**

## KEY CHARACTERISTICS

- Specific density: 1,095 g/ml
- Concentrate
- For sheetfed, heatset and coldset application
- pH value: 5
- Suited for all plate types
- Lasting plate protection

## FEATURES AND BENEFITS

### Wide application range

- Can be used with all plate types
- Conventional and CTP
- Positive and negative

## PACKAGING

10L jerrycan  
4 x 5L jerrycan  
12 x 1L plastic bottle

## INSTRUCTIONS FOR USE

Apply the plate gum with a sponge on the printing plate. When a change in viscosity is needed, plate gum can be diluted 1:1 with water where necessary for automatic systems.

## TRANSPORT & STORAGE

Protect against extreme weather conditions.

Do not store at temperature above 35 °C or below -10 °C.

Take all necessary precautions to avoid environmental pollution due to accidental leakage.

Version 1.0, state 19/09/2011 - All data contained in this technical information sheet is based upon lab tests and practical experience. The user is aware that user specific circumstances may influence the results. This technical information sheet is made for information purposes only and it does not constitute a warranty or guarantee in relation to the correctness or completeness of the data. Errors, omissions and literal mistakes excepted, subject to modifications at any time. The user acknowledges that the data contained herein is only effective as long as no updated technical information sheet is issued which replaces and supersedes any former version of this technical information sheet.