

SYSTEMCLEANER 1397

Cleaning concentrate for the dampening water circuit

KEY CHARACTERISTICS

- Dosage: 5 - 20 %
- Not foaming
- For sheetfed, heatset and coldset application
- pH value: 7
- Removes contamination of the dampening water circuit

FEATURES AND BENEFITS

Not foaming

- Avoid foaming of the fountain solution after cleaning

Universal in use

- Compatible with all fountain solutions

PACKAGING

25L jerrycan

10L jerrycan

INSTRUCTIONS FOR USE

Mix 5 - 20 % with pure water, depending on the grade of pollution. Let this solution circulate through the dampening system for 3 - 4 hours, after it has been drained from the fountain solution. Then drain off the cleaning solution and rinse the system several times with pure water, before refilling with fresh fountain solution. Cleaning with hot water not recommended.

TRANSPORT & STORAGE

Protect against extreme weather conditions.

Do not store at temperature above 35 °C or below -10 °C.

Take all necessary precautions to avoid environmental pollution due to accidental leakage.

For details about health and safety, please consult the MSDS.

Version 1.0, state 19/09/2011 - All data contained in this technical information sheet is based upon lab tests and practical experience. The user is aware that user specific circumstances may influence the results. This technical information sheet is made for information purposes only and it does not constitute a warranty or guarantee in relation to the correctness or completeness of the data. Errors, omissions and literal mistakes excepted, subject to modifications at any time. The user acknowledges that the data contained herein is only effective as long as no updated technical information sheet is issued which replaces and supersedes any former version of this technical information sheet.