



乐凯华光印刷科技有限公司

LUCKY HUAGUANG GRAPHIS CO., LTD

TEL: 0086-377-63863074 FAX: 0086-377-63138450 E-mail: ej-jck@hgfilm.com.cn

Add: 718 South Station Road, Nanyang, Henan, China

Huaguang UV-CTP plate UV-PH Technical specifications

Plate Type	Commercial Positive UV-CTP Plate
Application	Commercial sheet-fed and rotary press printing
Substrat	Electrochemically grained and anodized aluminum
Gauge	0.15mm/0.20mm/0.25mm/0.30mm/0.40mm
Maximum short grain width	0.15mm: 1050mm 0.30/0.40mm: 1320mm
Spectral sensitivity	350-460nm UV light
	Especially 400-410 UV laser
Safelights	UV filtered or Yellow
Sensitivity	35-45mj/cm ²
Color change	Blue-Green to Pale Green after exposed
Development	Conductivity: min 55ms, max 70ms Temperature: 20-25 °C PH 13.00-13.40
Developer	Common positive offset plate developer
Plate data	Ra: 0.55-0.70um Coating weight: 2.0-2.4g/m ² Oxidation weight: 2.8-3.2g/m ²
Dot reproduction	2%-98% in 200 lines/inch
Finalimagecolour	Blue
Packaging	0.15mm 100 pieces/box 0.30/0.40mm 50 pieces/box if length <1030mm; 30 pieces/box if length ≥1030mm; 25 pieces/box if the area of each plate > 1 m ²
Shelf life	18 months when stored in a light-free area away from excessive cold, heat and high humidity
Run length	0.30/0.40 mm above 150,000 (Actual run length may vary according to press, ink and stock conditions.)