

# VARNISH RETARDER

**Retarder for ink duct coatings and inline coating unit**

## KEY CHARACTERISTICS

- Mix of solvents
- High boiling
- Slow evaporation
- Water miscible

## PACKAGING

12 x 1L plastic bottle  
10 L plastic can

## INSTRUCTIONS FOR USE

**Ink duct coating:** Additive for start up and refreshing. Dilute with water 1:1. Please do note the processing information of ink duct coatings.

**Inline coating:** If necessary add maximum 1,0% to slow down the drying.  
Not intended for regularly use, please respond to your Fujifilm contact person.

## TRANSPORT & STORAGE

Protect against extreme weather conditions.

Do not store at temperature above 35 °C or below -10 °C.

Take all necessary precautions to avoid environmental pollution due to accidental leakage.

## FEATURES AND BENEFITS

### For ink duct coatings

- Start up aid
- Refreshing of skin-dry coating

### For inline coating

- Drying retarder

Version 1.0, state 19/09/2011 - All data contained in this technical information sheet is based upon lab tests and practical experience. The user is aware that user specific circumstances may influence the results. This technical information sheet is made for information purposes only and it does not constitute a warranty or guarantee in relation to the correctness or completeness of the data. Errors, omissions and literal mistakes excepted, subject to modifications at any time. The user acknowledges that the data contained herein is only effective as long as no updated technical information sheet is issued which replaces and supersedes any former version of this technical information sheet.

FUJIFILM Europe NV  
Europark-Noord 21-22  
9100 Sint-Niklaas  
Belgium

T +32 3 760 02 00  
F +32 3 776 91 22  
marketing\_feb@fujifilm.eu  
www.fujifilm.eu/feb

**FUJIFILM**